



BIMUSS TECHNOLOGY

Committed to providing industrial solutions and required accessories

Bimuss Industrial Park,33# TY Road,Shandong,China

(86)15306313650

dls@bimuss.com

RO antiscalant BimuroPro 100

Technical Date Sheet

Product Description

BimuroPro 100 is a kind of antiscalant with high cost performance.

can be used to control the fouling of membrane separation system and reduce particle clogging.

Can control the formation of calcium carbonate, calcium sulfate, barium sulfate, etc.

It can prevent the scaling of calcium carbonate when LSI reaches 3.

BimuroPro 100especially applies to small RO system and good water quality

No adverse effects on the environment, especially suitable for the district where has special requirements on wastewater discharge.

Specification

Parameter	Specification
Appearance	Colorless to light yellow liquid
Specific gravity	1.00-1.10
pH(5% water solution)	2-4
Viscosity	1.79TP
Storage temperature	≥-12°C

Adding and controlling

BimuroPro 100 should be continuously added to the last level security filter. This product should be injected into the water supply pipe by diluting water tank or packing barrel. The operation parameters of the specific dosing ratio depends on the water quality and membrane system.You can ask dosing software or technical personnel determined.

Storage

Do not touch eyes and skin.More information please see the MSDS.

Document provided

TDS,COA,MSDS,B/L,Packing list.

Delivery information

Packing:Conventional packaging for 25kg plastic barrels or IBC barrels. If you have special needs, please contact your sales consultant.